MATERIAL SAFETY DATA SHEET

BIRCHWOOD CASEY•
BARRICADE• (formerly Sheath*)
(Solution used in BARRICADE• TAKE ALONGS)



1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **BARRICADE**• (formerly Sheath•) **TAKE-ALONGS**

PRODUCT PART NUMBERS: 33001, 33025, 33170, 33194, BTA25, BTA100, BTA2000

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: WARNING! Harmful if swallowed or inhaled. Irritating to eyes, skin, upper respiratory tract. Combustible liquid and vapor. Keep away from sparks and open flames.

APPEARANCE/ODOR: Opaque light brown liquid, kerosene odor

EYE CONTACT: Irritation upon direct contact.

SKIN CONTACT: Irritation and possible dermatitis.

INGESTION: Irritation to the gastrointestinal tract. Aspiration of mineral oil into the lungs can cause chemical pneumonia.

INHALATION: Inhalation of high vapor concentrations may cause central nervous system effects, and symptoms such as headache, dizziness, disorientation.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Description	CAS#	Weight	OSHA PEL*	OSHA PEL	ACGIH TLV	ACGIH TLV
		%	TWA	STEL/C	TWA	STEL/C
Severely Hydrotreated	64742-47-8	60	NE	NE	NE	NE
Heavy Naphthenic						
Distillate						
Mineral Oil	64742-52-5	15	5 mg/m^3	NE	5 mg/m ^{3(**)}	10 mg/m ^{3(**)}
Heavy Petroleum	Mixture	20	NE	NE	NE	NE
Oxygenates, Barium						
neutralized						
Propylene Glycol	107-98-2	4	100 mg/m ^{3(skin)}	NE	100 mg/m^3	150 mg/m ^{3-STEL}
Monomethyl Ether						_

TWA – Time-weighted Average STEL – Short-term exposure limit C – Ceiling

(skin) – skin designation means that harmful amounts may be absorbed through the skin

NE = not established NA = not applicable NDA = no data available

^{*} Certain States enforce PELs that were in place in 1989, but were later removed by the U.S. Supreme Court. Check with your State OSHA to determine which PEL is enforced in your State.

^{**} as "oil mist, mineral", sampled by a method that does not collect vapor

Page 2 of 4 DATE REVISED: 12/17/12 REVISION MSDS NO. 4

4. FIRST AID MEASURES

EYE CONTACT: Flush immediately with clean water. Continue for at least 15 minutes. Seek medical attention if necessary.

SKIN CONTACT: Remove contaminated clothing to avoid prolonged contact. Wash affected areas with water. Seek medical attention if irritation develops.

INGESTION: Call Poison Control Center immediately. Do not induce vomiting.

INHALATION: Remove from exposure. Seek medical attention if necessary if breathing is difficult.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASHPOINT: 111° F METHOD USED: Closed Cup

FLAMMABLE LIMITS (%): LFL: 1.0 UFL: 6.0

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, foam.

FIRE & EXPLOSION HAZARDS: Do not flood with water.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear approved SCBA and full turn-out gear.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Spilled material may present slipping hazard. Wear recommended protective equipment. Eliminate ignition sources. Ventilate area. Absorb material on dry sorbent. Scoop up for disposal using non-sparking tools only. DO NOT flush to sewers.

Review current local, state and federal laws, codes, statutes, and regulations to determine appropriate agencies to be notified, and the conditions under which they are to be notified. (See Section 13 for waste disposal comments).

7. HANDLING AND STORAGE

HANDLING: Avoid breathing mists or vapor. Avoid eye and skin contact. Prohibit smoking in the area and exclude sources of spark or open flame. Avoid static discharge. Wear protective equipment when handling product. Empty containers may still have product residue and combustible vapors. Keep out of the reach of children.

STORAGE: Store liquid in closed containers. Store in clean, fire-resistant storage area with good ventilation and not subject to high temperatures.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Use a NIOSH approved respirator (Full or half-face organic vapor/P95 cartridge type) if any of the occupational exposure limits in Section 3 may be exceeded.

EYE PROTECTION: safety glasses with side shields, goggles

PROTECTIVE GLOVES: neoprene or polyvinyl alcohol

BODY PROTECTION: NDA

VENTILATION: Use general/dilution or local exhaust ventilation as needed to ensure that occupational exposure limits are not exceeded.

OTHER PROTECTIVE EQUIPMENT: Eyewash

NOTE: All PPE should be selected on the basis of an exposure assessment performed by a competent person.

BIRCHWOOD CASEY
BARRICADE• (formerly Sheath*)
(Solution used in BARRICADE• TAKE ALONGS)

Page 3 of 4 DATE REVISED: 12/17/12 REVISION MSDS NO. 4

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: > 300°F SPECIFIC GRAVITY: (Water = 1): 0.825 VAPOR PRESSURE: NDA VOLATILE BY VOLUME: > 70%

VAPOR DENSITY: (Air = 1): >1 EVAPORATION RATE: (Ethyl Ether = 1): < 1

SOLUBILITY IN WATER: Immiscible pH: NA

APPEARANCE: Brown liquid ODOR: kerosene-like odor

10. STABILITY AND REACTIVITY

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid high temperatures and ignition sources.

INCOMPATIBILITY (materials to avoid): Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce carbon monoxide, carbon dioxide, sulfur oxides, various hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

There is no product based toxicological information for this product. Toxicology information is provided based on individual ingredients.

LD_{50s}, oral, rat: 5660 mg/kg (Propylene Glycol Monomethyl Ether)

TARGET ORGANS: Eyes, skin, lungs (irritant), CNS. Prolonged or repeated skin exposure may cause dermatitis.

Medical conditions that may be aggravated by exposure: Pre-existing skin, eye, respiratory, CNS disorders.

Carcinogenicity: IARC: 3* (mineral oil) NTP: None OSHA: None

*unclassifiable as to carcinogenicity in humans (for mineral oils, highly refined)

12. ECOLOGICAL INFORMATION

ECOTOXICITY: NDA

ENVIRONMENTAL FATE: NDA

13. DISPOSAL CONSIDERATIONS

Waste concentrate is assigned the EPA Hazardous Waste Number D001 (Ignitability). Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be dealt with by a licensed facility or waste hauler. Note: If incinerated, the resulting ash will contain extractable barium. A waste with extractable barium of 100 ppm or greater is assigned EPA Hazardous Waste Number D005 (Toxicity Characteristic – Barium).

14. TRANSPORT INFORMATION

D.O.T. HAZARDOUS MATERIALS DESCRIPTION AND PROPER SHIPPING NAME:

Flammable Liquid, N.O.S. (Naphtha, Petroleum) 3 / UN1993 / P.G. III Exceptions may apply: 49CFR 173.150

BIRCHWOOD CASEY

BARRICADE• (formerly Sheath*)

(Solution used in BARRICADE• TAKE ALONGS)

15. REGULATORY INFORMATION

TSCA (TOXIC SUBSTANCES CONTROL ACT): the materials in this product are listed on the TSCA Inventory.

CERCLA (Comprehensive Response compensation and Liability Act, 40 CFR 117, 302: Reportable Quantity - NDA

SARA TITLE III (Superfund Amendments and Authorization Act):

Section 311/312:

Immediate Health Effects: Yes Delayed Health Effects: No

Fire Hazard: Yes

Sudden Release of Pressure Hazard: No

Reactivity Hazard: No

Section 313 Reportable Ingredients: Propylene Glycol Monomethyl Ether, Barium compounds in heavy petroleum oxygenates (Barium < 1%).

STATE "RIGHT-TO-KNOW": This product may contain components cited on certain state lists. Consult with your individual State regarding this product's components.