



# SAFETY DATA SHEET

Part No. P0300CT (Aerosol)

DL1 Dri-Lube

## SECTION 1 - IDENTIFICATION

### 1.1 Product Identifier

Product Name : DL1 Dri-Lube  
Manufacturer Product Number : P0300CT  
Supplier Product Numbers : DL1

### 1.2 Other Means of Identification

Other Identifiers : Not Available

### 1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Sporting dry lubricant  
Restrictions on Use : None Identified

### 1.4 Supplier Details

	Manufacturer Details	Supplier Details
Company Name :		Bushnell Holdings Inc.

### 1.5 24 hr Emergency Phone Number

Emergency Number : Emergency Telephone Number (Hazardous Material/Dangerous Goods Transportation Emergency ONLY)

## SECTION 2 - HAZARDS IDENTIFICATION

### 2.1 Classification of the Substance or Mixture

Flam. Aerosol 1	H222	Physical Hazards	Flammable aerosol Category 1
Press. Gas (Diss.)	H280	Physical Hazards	Gases under pressure Dissolved gas
Eye Irrit. 2	H319	Health Hazards	Serious eye damage/eye irritation Category 2
Repr. 2	H361	Health Hazards	Reproductive toxicity Category 2
Stot Se 3	H336	Health Hazards	Specific target organ toxicity (single exposure) Category 3, Narcosis

### 2.2 Label Elements

Hazard Pictograms



GHS02



GHS04



GHS07



GHS08

Signal Word

**Danger**

Hazard Statements

H222 : Extremely flammable aerosol  
H280 : Contains gas under pressure; may explode if heated  
H319 : Causes serious eye irritation  
H336 : May cause drowsiness or dizziness  
H361 : Suspected of damaging fertility or the unborn child

Precautionary Statements

P202 : Do not handle until all safety precautions have been read and understood.

# SAFETY DATA SHEET

Part No. P0300CT (Aerosol)

## DL1 Dri-Lube

- P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 : Do not spray on an open flame or other ignition source.
- P251 : Pressurized container: Do not pierce or burn, even after use.
- P261 : Avoid breathing spray.
- P264 : Wash hands thoroughly after handling.
- P271 : Use only outdoors or in a well-ventilated area.
- P280 : Wear protective gloves and eye protection.
- P304+P340 : If inhaled: Remove person to fresh air and keep comfortable for breathing
- P305+P351+P338 : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P308+P313 : If exposed or concerned: Get medical advice/attention.
- P312 : Call physician if you feel unwell
- P337+P313 : If eye irritation persists: Get medical advice/attention.
- P403 : Store in a well-ventilated place.
- P410+P412 : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 : Dispose of contents/container to local regulations

### 2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

### 2.4 Unknown acute toxicity

41% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

41% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

6% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

## SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

### 3.1 Substance / Mixture

Substance / Mixture : Mixture

### 3.2 Composition

Substance name	CAS Number	% wt*	Classification
Acetone	67-64-1	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Propane	74-98-6	10 - 30	Flam. Gas 1, H220 Press. Gas (Diss.), H280
N-Butane	106-97-8	10 - 30	Flam. Gas 1, H220 Press. Gas (Diss.), H280
Isobutane	75-28-5	5 - 10	Flam. Gas 1, H220 Press. Gas (Diss.), H280
Toluene	108-88-3	0.1 - 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401

Full text of hazard classes and H-statements : see section 16

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

## SECTION 4 - FIRST-AID MEASURES

### 4.1 Description of First-Aid Measures

- General Measures : If exposed or concerned: Get medical advice/attention.
- Inhalation : Remove person to fresh air and keep comfortable for breathing.
- Skin Contact : Wash skin with plenty of water.

# SAFETY DATA SHEET

Part No. P0300CT (Aerosol)

## DL1 Dri-Lube

Eye Contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	: Call a poison center or a doctor if you feel unwell.
First-Aid Responder Protection	: Wear adequate personal protective equipment based on the nature and severity of the emergency.

### 4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Throat Irritation, Dermatitis, Central Nervous System Depression, Confusion, Skin Irritation, Headache, Dizziness, Narcosis, Drowsiness.
Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: Because of defatting properties, repeated skin contact can cause skin damage such as chap, dermatitis, inflammation and the formation of eczema.
Target Organs	: Central Nervous System, Eyes, Liver, Reproductive System, Respiratory System, Skin, Kidneys.

### 4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Medical Conditions Aggravated	: May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

## SECTION 5 - FIRE-FIGHTING MEASURES

### 5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media	: Water jet.

### 5.2 Specific Hazards Arising from the Chemical or Mixture

Hazardous Combustion Products	: Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
Specific Hazards During Firefighting	: Contents under pressure. Extremely flammable. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

### 5.3 Special Protective Actions for Fire-Fighters

Firefighting Instructions	: Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure.
Protection during Firefighting	: Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### 6.1 Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel	: No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Emergency Personnel	: Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

### 6.2 Environmental Precautions

Environmental Precautions	: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
---------------------------	---

### 6.3 Methods and Materials for Containment and Cleaning up

Containment Procedures	: Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents.
------------------------	--

## SAFETY DATA SHEET

## DL1 Dri-Lube

- Cleanup Procedures** : Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
- Other Information** : Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned.
- Prohibited Materials** : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

## SECTION 7 - HANDLING AND STORAGE

## 7.1 Precautions for Safe Handling

- General Handling Precautions** : KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.
- Hygiene Recommendations** : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

## 7.2 Conditions for Safe Storage Including Any Incompatibilities

- Storage Requirements** : Storage of individual cans should be done in an area below 55°C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended.
- Incompatibilities** : Segregate storage away from materials indicated in Section 10.
- NFPA 30B Classification** : This product is classified as a Level 3 Aerosol per NFPA 30B

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

## 8.1 Control Parameters

**N-Butane (106-97-8)**

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1000 ppm
OSHA	OSHA PEL (TWA) (ppm)	800 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1900
NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	800 ppm

**Propane (74-98-6)**

OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2100 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	1000 ppm

**Isobutane (75-28-5)**

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1000 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	800 ppm

**Acetone (67-64-1)**

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	250 ppm
ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	500 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>

## SAFETY DATA SHEET

## DL1 Dri-Lube

**Acetone (67-64-1)**

California	California PEL (TWA) (ppm)	500 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	1780 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	750 ppm
California	California PEL (Ceiling) (ppm)	3000 ppm
Biological Exposure Index	Acetone in urine, End of shift (Ns)	25 mg/l

**Toluene (108-88-3)**

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	20 ppm
ACGIH	ACGIH Ceiling (mg/m <sup>3</sup> )	150 ppm
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
NIOSH	US IDLH (ppm)	500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
California	California PEL (TWA) (mg/m <sup>3</sup> )	37 mg/m <sup>3</sup>
California	California PEL (TWA) (ppm)	10 ppm
California	California PEL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
California	California PEL (STEL) (ppm)	150 ppm
California	California PEL (Ceiling) (ppm)	500 ppm
Biological Exposure Index	Toluene in blood, Prior to last shift of workweek	0.02 mg/l
Biological Exposure Index	Toluene in urine, End of shift	0.03 mg/l
Biological Exposure Index	o-Cresol in urine (with hydrolysis), End of shift (B)	0.3 mg/g creatinine

**8.2 Exposure Controls****Engineering Measures**

: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.

**Personal Protective Equipment****Eye / Face Protection**

: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.

**Hand Protection**

: Chemical-resistant gloves, tested according to ASTM F903 - 17.

**Remarks**

: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.

**Skin and Body Protection**

: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.

**Respiratory Protection**

: An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits.

**Compliance**

: If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.

**Other Protective Equipment**

: Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

**Environmental Exposure Controls**

: Avoid release to the environment.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES****9.1 Physical Properties**

Boiling Point	> 55.60 °C	Melting / Freezing Point	> -95.00 °C
Flash Point, Liquid	> -17.20 °C	Flash Point, Propellant	-104.40 °C
Explosive Limits	LEL: 1.20 UEL: 12.80 vol %	Autoignition Temperature, Liquid	485.00 °C
Flammability	Extremely Flammable Aerosol	Density	0.706 g/cm <sup>3</sup>
Molecular Weight	Not Available	Weight	5.892 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBac=1)	Not Available
Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Pressurized Product	Heat Of Combustion	14129.73 BTU/lb
Appearance / Color	Clear, Colorless	Water Solubility	Not Available

# SAFETY DATA SHEET

Part No. P0300CT (Aerosol)

## DL1 Dri-Lube

Odor	Slight	Decomposition Temperature	Not Available
------	--------	---------------------------	---------------

### 9.2 Environmental Properties

Percent Volatile	93.25 % wt	VOC Regulatory	593.66 g/L (4.95 lbs/gal)
Percent VOC	35.55 % wt	VOC Actual	250.98 g/L (2.09 lbs/gal)
Percent HAP	0.55 % wt	HAP Content	3.88 g/L (0.03 lbs/gal)
Global Warming Potential	1.51 GWP	Maximum Incremental Reactivity	0.5688 g O3/g
Ozone Depletion Potential	0.00 ODP		

## SECTION 10 - STABILITY AND REACTIVITY

### 10.1 Reactivity

**Reactivity** : No specific test data related to reactivity is available for this products or its ingredients.

### 10.2 Chemical Stability

**Chemical Stability** : This product is stable.

### 10.3 Possibility of Hazardous Reactions

**Hazardous Reactions** : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

### 10.4 Conditions to Avoid

**Conditions to Avoid** : Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

### 10.5 Incompatible Materials

**Materials to Avoid** : Strong Oxidizing Agents, Strong Reducing Agents, Strong Acids, Halogen Compounds, Hydrogen Peroxide, Potassium Chlorate.

### 10.6 Hazardous Decomposition Products

**Thermal Decomposition** : Oxides of carbon, Aldehydes, Formaldehyde, Methanol, Acetic Acid.

## SECTION 11 - TOXICOLOGICAL INFORMATION

### 11.1 Information on Toxicological Effects

#### **N-Butane (CAS: 106-97-8 / EC: 203-448-7)**

LC50 Inhalation (Rat)	658 mg/l/4h (ChemInfo)
LC50 Inhalation (Rat)	276000 ppm/4h (ChemInfo)

#### **Propane (CAS: 74-98-6 / EC: 200-827-9)**

LC50 Inhalation (Rat)	658 mg/l/4h (Lit.)
-----------------------	--------------------

#### **Isobutane (CAS: 75-28-5 / EC: 200-857-2)**

LC50 Inhalation (Rat)	368000 ppm/4h (ChemInfo)
-----------------------	--------------------------

#### **Acetone (CAS: 67-64-1 / EC: 200-662-2)**

LD50 Oral (Rat)	5800 mg/kg (Sigma-Aldrich)
LD50 Dermal (Rabbit)	20000 mg/kg (IUCLID)
LC50 Inhalation (Rat)	76 mg/l/4h (GESTIS Substance Database)

#### **Toluene (CAS: 108-88-3 / EC: 203-625-9)**

LD50 Oral (Rat)	> 2000 mg/kg (Lit.)
LD50 Dermal (Rabbit)	12124 mg/kg (IUCLID)
LC50 Inhalation (Rat)	> 20 mg/l/4h (Lit.)

**Routes Of Exposure** : Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.

**Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure** : See Section 4.2

**Skin Corrosion/Irritation** : Not classified

## SAFETY DATA SHEET

## DL1 Dri-Lube

Eye Damage/Irritation	: Causes serious eye irritation.
Respiratory or Skin Sensitization	: Not classified
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Suspected of damaging fertility or the unborn child.
STOT-Single Exposure	: May cause drowsiness or dizziness.
STOT-Repeated Exposure	: Not classified
Aspiration Hazard	: Not classified
Vaporizer	: Aerosol
Carcinogen Data	: None of the ingredients in the product are listed with OSHA, IARC, NTP or ACGIH as being a suspected or known carcinogen in a concentration greater than 0.1% by weight.

## SECTION 12 - ECOLOGICAL INFORMATION

## 12.1 Ecotoxicity and Ecological Properties

**n-Butane (106-97-8)**

Persistence and Degradability	Readily biodegradable in water.
Bioconcentration Factor	33.52
Log Pow	2.89
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).
Log Koc	1.641

**Propane (74-98-6)**

Persistence and Degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.
BCF Fish	9 - 25 (BCF)
Log Pow	2.28 (Calculated)
Bioaccumulative Potential	Low potential for bioaccumulation (Log Kow < 4).

**Isobutane (75-28-5)**

Persistence and Degradability	Readily biodegradable in water. Biodegradable in the soil. Not applicable (gas).
BCF Fish	26.62
Log Pow	2.76
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	1.545

**Acetone (67-64-1)**

LC50 Fish	5540 mg/l Rainbow Trout - 96hr
LC50 Fish	8300 mg/l Bluegill Sunfish - 96h
EC50 Daphnia	8800 mg/l Water Flea - 48hr
Persistence and Degradability	Biodegradability 90% / 28 days.
Biochemical Oxygen Demand	1.43 g O <sub>2</sub> /g substance
Chemical Oxygen Demand	1.92 g O <sub>2</sub> /g substance
Theoretical Oxygen Demand	2.2 g O <sub>2</sub> /g substance
BCF Fish	0.69
BCF Other Aquatic Organisms	3
Log Pow	-0.24

**Toluene (108-88-3)**

LC50 Fish	5.8 mg/l Rainbow Trout - 96hr
LC50 Other Aquatic Organisms	10 mg/l Green Algae - 72hr
EC50 Daphnia	6 mg/l Water Flea - 48hr
Persistence and Degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for absorption in soil.
Biochemical Oxygen Demand	2.15 g O <sub>2</sub> /g substance
Chemical Oxygen Demand	2.52 g O <sub>2</sub> /g substance
Theoretical Oxygen Demand	3.13 g O <sub>2</sub> /g substance
Biodegradation	86 % 28 Days
Log Pow	2.73 (Experimental Value)
Bioaccumulative Potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	2.15

# SAFETY DATA SHEET

Part No. P0300CT (Aerosol)

**DL1 Dri-Lube**

## SECTION 13 - DISPOSAL CONSIDERATIONS

### 13.1 Waste Treatment Methods

- Waste Disposal** : Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
- Waste Disposal Of Packaging** : In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.
- Landfill Precautions** : Not Available.
- Incineration Precautions** : **\*\* DO NOT INCINERATE \*\* CONTENTS UNDER PRESSURE \*\*.**

## SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
----------------	-----------	------------	--------------

UN Number	: UN1950	UN1950	UN1950
-----------	----------	--------	--------

14.2 UN Proper Shipping Name	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
------------------------------	-----------	------------	--------------

UN Proper Shipping Name	: Aerosols, Limited Quantity	Aerosols, Flammable, Limited Quantity	Aerosols, Limited Quantity
-------------------------	------------------------------	---------------------------------------	----------------------------

14.3 Transport Hazard Class(es)	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
---------------------------------	-----------	------------	--------------

Transport Hazard Class(es)	: 2.1	2.1	2.1
Labels	: None	2.1 - Flammable gas	None

Limited Quantity	: Yes	Yes	Yes
------------------	-------	-----	-----



EmS Code	: Not Applicable	Not Applicable	F-D, S-U
----------	------------------	----------------	----------

14.4 Packing Group	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
--------------------	-----------	------------	--------------

Packing Group	: None	None	None
---------------	--------	------	------

14.5 Environmental Hazards	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
----------------------------	-----------	------------	--------------

Marine Pollutant	: No	No	No
------------------	------	----	----

### 14.6 Special Precautions

Precautions : None Identified

### 14.7 Transport in Bulk

Remarks : Not applicable for product as supplied

## SECTION 15 - REGULATORY INFORMATION

### 15.1 Federal Regulations

**SARA Section 313** : Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene	CAS-No. 108-88-3	< 1%
---------	------------------	------



# SAFETY DATA SHEET

Part No. P0300CT (Aerosol)

## DL1 Dri-Lube

**TSCA Section 12(b)** : This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D

**CERCLA Reportable Quantity** : Chemical(s) subject to reporting requirements of Section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) if released to the environment at or above the reportable quantity

Acetone	CAS-No. 67-64-1	5000 lb
Toluene	CAS-No. 108-88-3	1000 lb

**TSCA Inventory (United States)** : All chemical substances in this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are in compliance with a TSCA Inventory exemption.

### 15.2 State Regulations

**California Proposition 65** : This product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

Toluene (108-88-3)	Developmental Toxicity	Yes	0.55 %
Toluene (108-88-3)	No significance risk level (NSRL)	7000	

**State Right-to-Know Lists** : The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

n-Butane (106-97-8)	U.S. - New Jersey - Right to Know Hazardous Substance List
Propane (74-98-6)	U.S. - New Jersey - Right to Know Hazardous Substance List
Isobutane (75-28-5)	U.S. - New Jersey - Right to Know Hazardous Substance List
Acetone (67-64-1)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Toluene (108-88-3)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Polytetrafluoroethylene (9002-84-0)	U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List

## SECTION 16 - OTHER INFORMATION

**Indication of changes** :

Section	Changed item	Change
1	Revision date	Modified
1	Supersedes	Modified
1	Change to Supplier Details	Modified

**Full Text of H-Statements** :

H Code	H Phrase
H220	Extremely flammable gas
H225	Highly flammable liquid and vapour
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life