



SAFETY DATA SHEET

Part No. P0305CT (Aerosol)

MDL

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : MDL
Manufacturer Product Number : P0305CT

1.2 Other Means of Identification

Other Identifiers : Not Available

1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Gun Lubricant
Restrictions on Use : None Identified

1.4 Supplier Details

	Manufacturer Details	Supplier Details
Company Name :		Bushnell Holdings Inc.


SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Flam. Aerosol 1	H222	Physical Hazards	Flammable aerosol Category 1
Press. Gas (Diss.)	H280	Physical Hazards	Gases under pressure Dissolved gas
Eye Irrit. 2	H319	Health Hazards	Serious eye damage/eye irritation Category 2
Stot Se 3	H336	Health Hazards	Specific target organ toxicity (single exposure) Category 3, Narcosis
Asp. Tox. 1	H304	Health Hazards	Aspiration hazard Category 1
Aquatic Acute 2	H401	Environmental Hazards	Hazardous to the aquatic environment - Acute Hazard Category 2

2.2 Label Elements

Hazard Pictograms



Signal Word

Danger

Hazard Statements

H222 : Extremely flammable aerosol
H280 : Contains gas under pressure; may explode if heated
H304 : May be fatal if swallowed and enters airways
H319 : Causes serious eye irritation
H336 : May cause drowsiness or dizziness
H401 : Toxic to aquatic life

SAFETY DATA SHEET

Part No. P0305CT (Aerosol)

MDL

Precautionary Statements	P210	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	: Do not spray on an open flame or other ignition source.
	P251	: Pressurized container: Do not pierce or burn, even after use.
	P261	: Avoid breathing spray.
	P264	: Wash hands thoroughly after handling.
	P271	: Use only outdoors or in a well-ventilated area.
	P273	: Avoid release to the environment.
	P280	: Wear protective gloves and eye protection.
	P301+P310	: If swallowed: Immediately call POISON CENTER
	P304+P340	: If inhaled: Remove person to fresh air and keep comfortable for breathing
	P305+P351+P338	: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
	P312	: Call physician if you feel unwell
	P331	: Do NOT induce vomiting.
	P337+P313	: If eye irritation persists: Get medical advice/attention.
	P403	: Store in a well-ventilated place.
P410+P412	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P501	: Dispose of contents/container to local regulations	

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

2.4 Unknown acute toxicity

12% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
12% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance / Mixture

Substance / Mixture : Mixture

3.2 Composition

Substance name	CAS Number	% wt*	Classification
Hydrotreated Light Petroleum Distillate	64742-47-8	>= 30	Asp. Tox. 1, H304 Aquatic Acute 2, H401
Acetone	67-64-1	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Hydrotreated Heavy Paraffinic Distillate	64742-54-7	5 - 30	Asp. Tox. 1, H304
Propane	74-98-6	5 - 10	Flam. Gas 1, H220 Press. Gas (Diss.), H280
N-Butane	106-97-8	1 - 5	Flam. Gas 1, H220 Press. Gas (Diss.), H280
Isobutane	75-28-5	1 - 5	Flam. Gas 1, H220 Press. Gas (Diss.), H280

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 - FIRST-AID MEASURES

4.1 Description of First-Aid Measures

General Measures	: Call a physician immediately.
Inhalation	: Remove person to fresh air and keep comfortable for breathing.
Skin Contact	: Wash skin with plenty of water.
Eye Contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SAFETY DATA SHEET

Part No. P0305CT (Aerosol)

MDL

Ingestion : Do NOT induce vomiting. Call a physician immediately.
First-Aid Responder Protection : Wear adequate personal protective equipment based on the nature and severity of the emergency.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure : Eye Irritation, Nose Irritation, Throat Irritation, Dermatitis, Central Nervous System Depression, Confusion, Headache, Dizziness, Narcosis, Drowsiness, Chemical Pneumonitis (Aspiration Liquid).
Delayed Effects : No known delayed effects.
Immediate Effects : No known immediate effects.
Chronic Effects : Because of defatting properties, repeated skin contact can cause skin damage such as chap, dermatitis, inflammation and the formation of eczema.
Target Organs : Central Nervous System, Eyes, Respiratory System, Skin.

4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician : Treat symptomatically.
Specific Treatments/Antidotes : No Information Available.
Medical Conditions Aggravated : May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media : Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media : Water jet.

5.2 Specific Hazards Arising from the Chemical or Mixture

Hazardous Combustion Products : Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
Specific Hazards During Firefighting : Contents under pressure. Extremely flammable. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

5.3 Special Protective Actions for Fire-Fighters

Firefighting Instructions : Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure.
Protection during Firefighting : Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel : No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Emergency Personnel : Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

6.2 Environmental Precautions

Environmental Precautions : Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

6.3 Methods and Materials for Containment and Cleaning up

Containment Procedures : Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents.
Cleanup Procedures : Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.

SAFETY DATA SHEET

MDL

- Other Information** : Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned.
- Prohibited Materials** : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions for Safe Handling

- General Handling Precautions** : KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.
- Hygiene Recommendations** : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

7.2 Conditions for Safe Storage Including Any Incompatibilities

- Storage Requirements** : Storage of individual cans should be done in an area below 55°C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended.
- Incompatibilities** : Segregate storage away from materials indicated in Section 10.
- NFPA 30B Classification** : This product is classified as a Level 3 Aerosol per NFPA 30B

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

N-Butane (106-97-8)

ACGIH	ACGIH TWA (mg/m ³)	1000 ppm
OSHA	OSHA PEL (TWA) (ppm)	800 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	1900
NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
California	California PEL (TWA) (mg/m ³)	1900 mg/m ³
California	California PEL (TWA) (ppm)	800 ppm

Propane (74-98-6)

OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2100 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	1800 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
California	California PEL (TWA) (mg/m ³)	1800 mg/m ³
California	California PEL (TWA) (ppm)	1000 ppm

Isobutane (75-28-5)

ACGIH	ACGIH TWA (mg/m ³)	1000 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	800 ppm

Hydrotreated Heavy Paraffinic Distillate (64742-54-7)

ACGIH	ACGIH TWA (ppm)	5 mg/m ³ Oil Mist
OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ Oil Mist
California	California PEL (TWA) (mg/m ³)	5 mg/m ³

Acetone (67-64-1)

ACGIH	ACGIH TWA (mg/m ³)	250 ppm
ACGIH	ACGIH Ceiling (mg/m ³)	500 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm

SAFETY DATA SHEET

Part No. P0305CT (Aerosol)

MDL

Acetone (67-64-1)		
California	California PEL (TWA) (mg/m ³)	1200 mg/m ³
California	California PEL (TWA) (ppm)	500 ppm
California	California PEL (STEL) (mg/m ³)	1780 mg/m ³
California	California PEL (STEL) (ppm)	750 ppm
California	California PEL (Ceiling) (ppm)	3000 ppm
Biological Exposure Index	Acetone in urine, End of shift (Ns)	25 mg/l

8.2 Exposure Controls

- Engineering Measures** : Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
- Personal Protective Equipment**
- Eye / Face Protection** : Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
- Hand Protection** : Chemical-resistant gloves, tested according to ASTM F903 - 17.
- Remarks** : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.
- Skin and Body Protection** : For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
- Respiratory Protection** : An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits.
- Compliance** : If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.
- Other Protective Equipment** : Safety showers and eye-wash stations should be available in the workplace near where the material will be used.
- Environmental Exposure Controls** : Avoid release to the environment.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 55.60 °C	Melting / Freezing Point	> 94.40 °C
Flash Point, Liquid	> -17.20 °C	Flash Point, Propellant	-104.40 °C
Explosive Limits	LEL: 0.60 UEL: 12.80 vol %	Autoignition Temperature, Liquid	231.00 °C
Flammability	Extremely Flammable Aerosol	Density	0.766 g/cm ³
Molecular Weight	Not Available	Weight	6.392 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBac=1)	Not Available
Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Pressurized Product	Heat Of Combustion	17949.14 BTU/lb
Appearance / Color	Clear, Colorless	Water Solubility	Not Available
Odor	Slight	Decomposition Temperature	Not Available

9.2 Environmental Properties

Percent Volatile	87.40 % wt	VOC Regulatory	297.32 g/L (2.48 lbs/gal)
Percent VOC	12.00 % wt	VOC Actual	91.92 g/L (0.77 lbs/gal)
Percent HAP	0.00 % wt	HAP Content	0.00 g/L (0.00 lbs/gal)
Global Warming Potential	0.54 GWP	Maximum Incremental Reactivity	0.7430 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

SAFETY DATA SHEET

MDL

10.2 Chemical Stability

Chemical Stability : This product is stable.

10.3 Possibility of Hazardous Reactions

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 Conditions to Avoid

Conditions to Avoid : Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

10.5 Incompatible Materials

Materials to Avoid : Strong Oxidizing Agents, Strong Reducing Agents, Strong Acids, Halogen Compounds, Hydrogen Peroxide.

10.6 Hazardous Decomposition Products

Thermal Decomposition : Oxides of carbon, Formaldehyde, Methanol, Acetic Acid.

SECTION 11 - TOXICOLOGICAL INFORMATION**11.1 Information on Toxicological Effects****N-Butane (CAS: 106-97-8 / EC: 203-448-7)**

LC50 Inhalation (Rat)	658 mg/l/4h (ChemInfo)
LC50 Inhalation (Rat)	276000 ppm/4h (ChemInfo)

Propane (CAS: 74-98-6 / EC: 200-827-9)

LC50 Inhalation (Rat)	658 mg/l/4h (Lit.)
-----------------------	--------------------

Isobutane (CAS: 75-28-5 / EC: 200-857-2)

LC50 Inhalation (Rat)	368000 ppm/4h (ChemInfo)
-----------------------	--------------------------

Hydrotreated Light Petroleum Distillate (CAS: 64742-47-8 / EC: 265-149-8)

LD50 Oral (Rat)	> 5000 mg/kg (ExxonMobil SDS)
LD50 Dermal (Rabbit)	> 5000 mg/kg (ExxonMobil SDS)
LC50 Inhalation (Rat)	> 5000 mg/kg (ExxonMobil SDS)

Hydrotreated Heavy Paraffinic Distillate (CAS: 64742-54-7 / EC: 256-157-1)

LD50 Oral (Rat)	> 5000 mg/kg (ChemInfo)
LD50 Dermal (Rabbit)	> 2000 mg/kg (ChemInfo)
LC50 Inhalation (Rat)	2180 ml/m ³ (RTECS)

Acetone (CAS: 67-64-1 / EC: 200-662-2)

LD50 Oral (Rat)	5800 mg/kg (Sigma-Aldrich)
LD50 Dermal (Rabbit)	20000 mg/kg (IUCLID)
LC50 Inhalation (Rat)	76 mg/l/4h (GESTIS Substance Database)

Routes Of Exposure : Eye Contact, Ingestion, Skin Contact, Inhalation.

Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure : See Section 4.2

Skin Corrosion/Irritation : Not classified

Eye Damage/Irritation : Causes serious eye irritation.

Respiratory or Skin Sensitization : Not classified

Germ Cell Mutagenicity : Not classified

Reproductive Toxicity : Not classified

STOT-Single Exposure : May cause drowsiness or dizziness.

STOT-Repeated Exposure : Not classified

Aspiration Hazard : May be fatal if swallowed and enters airways.

Vaporizer : Aerosol

Carcinogen Data : None of the ingredients in the product are listed with OSHA, IARC, NTP or ACGIH as being a suspected or known carcinogen in a concentration greater than 0.1% by weight.

SAFETY DATA SHEET

Part No. P0305CT (Aerosol)

MDL

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity and Ecological Properties

n-Butane (106-97-8)	
<i>Persistence and Degradability</i>	<i>Readily biodegradable in water.</i>
<i>Bioconcentration Factor</i>	33.52
<i>Log Pow</i>	2.89
<i>Bioaccumulative Potential</i>	<i>Low potential for bioaccumulation (Log Kow < 4).</i>
<i>Log Koc</i>	1.641

Propane (74-98-6)	
<i>Persistence and Degradability</i>	<i>Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.</i>
<i>BCF Fish</i>	9 - 25 (BCF)
<i>Log Pow</i>	2.28 (Calculated)
<i>Bioaccumulative Potential</i>	<i>Low potential for bioaccumulation (Log Kow < 4).</i>

Isobutane (75-28-5)	
<i>Persistence and Degradability</i>	<i>Readily biodegradable in water. Biodegradable in the soil. Not applicable (gas).</i>
<i>BCF Fish</i>	26.62
<i>Log Pow</i>	2.76
<i>Bioaccumulative Potential</i>	<i>Low potential for bioaccumulation (BCF < 500).</i>
<i>Log Koc</i>	1.545

Hydrotreated Light Petroleum Distillate (64742-47-8)	
<i>LC50 Fish</i>	<i>2.9 mg/l Rainbow Trout - 96hr</i>
<i>Persistence and Degradability</i>	<i>Biodegradability 88% / 28 days.</i>
<i>Biodegradation</i>	<i>85 % 28 Days</i>
<i>Log Pow</i>	6

Hydrotreated Heavy Paraffinic Distillate (64742-54-7)	
<i>LC50 Fish</i>	<i>> 5000 mg/l Rainbow Trout - 96hr</i>
<i>EC50 Daphnia</i>	<i>> 1000 mg/l Water Flea - 48hr</i>
<i>Persistence and Degradability</i>	<i>Biodegradability in water: no data available.</i>
<i>Log Pow</i>	<i>> 6.5</i>
<i>Bioaccumulative Potential</i>	<i>No bioaccumulation data available.</i>

Acetone (67-64-1)	
<i>LC50 Fish</i>	<i>5540 mg/l Rainbow Trout - 96hr</i>
<i>LC50 Fish</i>	<i>8300 mg/l Bluegill Sunfish - 96h</i>
<i>EC50 Daphnia</i>	<i>8800 mg/l Water Flea - 48hr</i>
<i>Persistence and Degradability</i>	<i>Biodegradability 90% / 28 days.</i>
<i>Biochemical Oxygen Demand</i>	<i>1.43 g O₂/g substance</i>
<i>Chemical Oxygen Demand</i>	<i>1.92 g O₂/g substance</i>
<i>Theoretical Oxygen Demand</i>	<i>2.2 g O₂/g substance</i>
<i>BCF Fish</i>	0.69
<i>BCF Other Aquatic Organisms</i>	3
<i>Log Pow</i>	-0.24

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

- | | |
|------------------------------------|--|
| Waste Disposal | : <i>Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.</i> |
| Waste Disposal Of Packaging | : <i>In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.</i> |
| Landfill Precautions | : <i>Not Available.</i> |

SAFETY DATA SHEET

Part No. P0305CT (Aerosol)

MDL

Incineration Precautions : **** DO NOT INCINERATE ** CONTENTS UNDER PRESSURE **.**

SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number DOT (USA) IATA (AIR) IMDG (OCEAN)

UN Number : UN1950 UN1950 UN1950

14.2 UN Proper Shipping Name DOT (USA) IATA (AIR) IMDG (OCEAN)

UN Proper Shipping Name : Aerosols, Limited Quantity Aerosols, Flammable, Limited Quantity Aerosols, Limited Quantity

14.3 Transport Hazard Class(es) DOT (USA) IATA (AIR) IMDG (OCEAN)

Transport Hazard Class(es) : 2.1 2.1 2.1

Labels : None 2.1 - Flammable gas None

Limited Quantity : Yes Yes Yes



EmS Code : Not Applicable Not Applicable F-D, S-U

14.4 Packing Group DOT (USA) IATA (AIR) IMDG (OCEAN)

Packing Group : None None None

14.5 Environmental Hazards DOT (USA) IATA (AIR) IMDG (OCEAN)

Marine Pollutant : No No No

14.6 Special Precautions

Precautions : None Identified

14.7 Transport in Bulk

Remarks : Not applicable for product as supplied

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations

SARA Section 313 : This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

TSCA Section 12(b) : This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D

CERCLA Reportable Quantity : Chemical(s) subject to reporting requirements of Section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) if released to the environment at or above the reportable quantity

Acetone	CAS-No. 67-64-1	5000 lb
---------	-----------------	---------

TSCA Inventory (United States) : All chemical substances in this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are in compliance with a TSCA Inventory exemption.

SAFETY DATA SHEET

Part No. P0305CT (Aerosol)

MDL

15.2 State Regulations

California Proposition 65 : This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

State Right-to-Know Lists : The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

<i>n</i> -Butane (106-97-8)	U.S. - New Jersey - Right to Know Hazardous Substance List
Propane (74-98-6)	U.S. - New Jersey - Right to Know Hazardous Substance List
Isobutane (75-28-5)	U.S. - New Jersey - Right to Know Hazardous Substance List
Acetone (67-64-1)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 - OTHER INFORMATION

Indication of changes

Section	Changed item	Change
1	Supersedes	Modified
1	Change to Supplier Details	Modified
1	Revision date	Modified

Full Text of H-Statements

H Code	H Phrase
H220	Extremely flammable gas
H225	Highly flammable liquid and vapour
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H401	Toxic to aquatic life