















265 Lumens

The Nightstick MT-220 Mini-TAC Pro uses an LED and has a deep parabolic reflector creating a tight, long throw beam for distance illumination. With a waterproof design, this light is constructed from aircraft-grade 6061-T6 aluminum with a Type III hard anodized finish. The tail switch provides momentary or constant-on functionality, a set of user-selectable high, medium or low-brightness settings as well as a disorienting strobe. The light comes with a removable pocket clip and is powered by two AA batteries.



MT-220

- Momentary or constant-on, plus 3 user-selectable brightness settings plus strobe
- Aircraft-grade 6061-T6 aluminum housing
- Small light-weight design








High-efficiency deep parabolic reflector

FEATURES

- LED technology 50,000 + hours
- Momentary or constant-on flashlight plus 3 brightness levels & strobe
- Sharp focused flashlight beam
- Aircraft-grade 6061-T6 aluminum
- Type III hard anodized finish
- Non-slip grip
- Waterproof
- Impact & chemical resistant
- Meets the requirements of NFPA-1971-8.6 (2013)
- Powered by: 2 AA batteries
- Limited Lifetime Warranty*

MT-220 SPECIFICATIONS







■ Length: 6in, head diameter: 0.9in, handle diameter: 0.6in, weight: 3.2oz



Handheld



High-efficiency deep parabolic reflector



Large textured tail-switch

INCLUDED

- Flashlight
- Removable pocket clip
- 2 AA batteries



Model	Description	UPC 0 17398
MT-220	Mini-TAC Pro flashlight with 2 AA battery, and removable pocket clip	80374 8



MT-220 Mini-TAC Pro

MARKET APPLICATIONS

Law enforcement, fire & rescue, industrial, security, hardware/tool, automotive, hunting/recreation.

DESCRIPTION

CASE MATERIAL

This non-rechargeable Mini-TAC Pro light uses an LED and has a deep parabolic reflector creating a tight, long throw beam for distance illumination. With a waterproof design, it is constructed from aircraft-grade 6061-T6 aluminum with a Type III hard anodized finish. The tail switch provides momentary or constant-on functionality, a set of user-selectable high, medium or low-brightness settings as well as a disorienting strobe. The light come with a removable pocket clip and is powered by two included AA batteries. Meets requirements of NFPA-1971-8.6 (2013).

Aircraft-grade 6061-T6 Aluminum with a Type III Hard Anodized Finish - Black

DIMENSIONS Length: 6 inches (152 mm) • Handle diameter: 0.6 inches (15 mm) • Head diameter: 0.9 inches (23 mm)

WEIGHT Weight: 3.2 oz. (91 g) with batteries installed.

LIGHT SOURCE

LIGHT OUTPUT

Unbreakable polycarbonate with scratch resistant coating.

LED. Impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT

High - 265 lumens, Medium - 130 lumens, Low - 90 lumens

0N/0FF Single Tail Cap Switch - Momentary or Constant-on Flashlight, High, Medium and Low-Brightness Flashlight, Strobe

RUN-TIME High - 2.5 hours, Medium - 8 hours, Low - 18 hours

BATTERY 2 AA Premium Batteries (included) **FEATURES** • LED technology – 50,000+ hours

• Momentary or constant-on, plus 3 user-selectable brightness settings plus strobe

· Sharp focused flashlight beam

· Aircraft-grade 6061-T6 aluminum housing

• Type III hard anodized finish

Non-slip gripWaterproof

Impact and chemical resistant

• Meets requirements of NFPA-1971-8.6 (2013)

· Powered by 2 AA batteries (included)

WARRANTY APPROVALS Limited Lifetime Warranty

(6

FL1 STANDARD	нібн	MEDIUM	LOW
314	265 LUMENS	130 LUMENS	90 LUMENS
(1)	2h 30min	8h	18h
	100m	73m	56m
	2486cd	1335cd	797cd
2m /			

