

2 CR123

DUAL-LIGHT™ HELMET LIGHT

NSP-4650B

NIGHTSTICK
Life Depends on Light™

NEW 360° MOUNT

Positions light **at any angle** and **holds firm**.

MEETS

NFPA
1971-8.6 (2013)
REQUIREMENTS



Provides **maximum versatility and safety**.

DUAL-LIGHT™ POWERFUL SPOTLIGHT AND 45° FLOODLIGHT



The durable **integrated brim mount** clamps securely to nearly all helmets.




360-degree mount provides user infinite aiming options, as well as clearance for external shields.



Helmet clamp features **no-mar rubber foot** for robust grip and peace of mind.



Large spotlight and floodlight buttons are **designed to be activated with gloved hand**.



220 LUMENS

DUAL-LIGHT™ HELMET LIGHT

2 CR123

ITEM NUMBER/UPC

NSP-4650B - 017398804714

CERTIFICATIONS

- CE
- NFPA 1971-8.6 (2013)

CASE MATERIAL

- 6061-T6 aluminum

LUMENS/RUNTIME

SPOTLIGHT

- HIGH: 220L, 3.5 hrs. runtime
- MEDIUM: 100L, 10 hrs. runtime
- LOW (SURVIVAL MODE) 30L: 33.5 hrs. runtime

FLOODLIGHT

- HIGH: 100L, 10 hrs. runtime
- MEDIUM: 50L, 21.5 hrs. runtime
- LOW (SURVIVAL MODE) 15L: 60 hrs. runtime

DUAL-LIGHT

- 175L, 4.5 hrs. runtime

CANDELA

- HIGH: 8,073
- MEDIUM: 3,669
- LOW: 861

BEAM DISTANCE

SPOTLIGHT

- HIGH: 183m
- MEDIUM: 120m
- LOW: 59m

WATER RATING

- IP-X7 (waterproof)

DROP RATING

- 2 meters

DIMENSIONS






- LENGTH: 3.2 in (81mm)
- WIDTH: 1.4 in (36mm)
- DEPTH: 3.2 in (81mm)
- BEZEL DIAMETER: 1.1 in (28mm)
- WEIGHT: 7.2 oz (204g)

BATTERY

- 2 CR123 batteries (included)

WHAT'S INCLUDED

- Helmet Light
- 2 CR123 batteries
- Allen wrench
- Instruction manual

FL1 STANDARD	FLASH	FLOOD	DUAL-LIGHT
	220 LUMENS	100 LUMENS	175 LUMENS
	3h 30min	10h	4h 30min
	183m		
	8073cd		
	2m		
	1m		
CERTIFIED			
	NFPA	CE	