

1200 Protector

Sensitive equipment needs protection, and since 1976 the answer has been the Pelican[™] Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the arctic or the heat of battle, Pelican cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

• Watertight, crushproof, and dustproof

Automatic Pressure Equalization Valve - balances interior pressure, keeps water out

- Easy open Double Throw latches
- Lifetime Guarantee of Excellence
- O-ring seal
- Open cell core with solid wall design strong, light weight
- Pick N Pluck[™] with convoluted lid foam
- Stainless steel hardware



CONFIGURATIONS



1200 Standard



1200NF No Foam



1200WF With Foam

DIMENSIONS

9.25 x 7.12" x 4.12 (23.5 x 18.1 x 10.5 cm)
10.62 x 9.68" x 4.87 (27 x 24.6 x 12.4 cm)
1.18" (3 cm)
2.93" (7.4 cm)
4.11" (10.4 cm)
0.16 ft ³ (0.005 m ³)

MATERIALS

Body	Polypropylene
Latch	ABS
O-Ring	Polymer
Pins	Stainless Steel
Foam	1.3 lb Polyurethane
Purge Body	ABS
Purge Vent	3 Micron Hydrophobic Non-Woven

COLORS



WEIGHT

Weight With Foam	2.87 lbs (1.3 kg)
Weight Empty	2.65 lbs (1.2 kg)
Buoyancy	12.02 lbs (5.5 kg)
Master Pack Weight	25.00 lbs (11.3 kg)

TEMPERATURE

Minimum Temperature	-40°F (-40 °C)
Maximum Temperature	210°F (98.9 °C)

CERTIFICATIONS

IP67			
Def Stan 81-41			
STANAG 4280			

FOAM PROPERTIES

Layer 1 (Lid)	1.38" Convolute
Layer 2 (Base)	0.56" Pad
Layer 3 (Base)	2.19" Pick N Pluck

OTHER

Master Pack	6
Military	yes

ACCESSORIES



1201 3 pc. Replacement Foam Set



1507 Quick Mounts - set of 4



1203 Replacement O-ring



1506TSA TSA Lock



1200PF Special Application Panel Frame



1500D Desiccant Silica Gel



1200TPKIT TrekPak Case Divider Kit



1120TPDIV Extra TrekPak Dividers