# **Technical Bulletin**



**DATE: MARCH 20, 2014** 

TITLE: PELICAN PROGEAR 2360 LED FLASHLIGHT NOW FEATURES AN ADDITIONAL

PERFORMANCE INCREASE

PRODUCTS AFFECTED: PELICAN PROGEAR 2360 LED FLASHLIGHT

#### **DETAILS:**

The Pelican ProGear<sup>™</sup> 2360 LED Flashlight has received an additional LED upgrade that increases the performance in the following categories, while retaining the <u>same price</u>:



	Generation 3		Generation 4	
	High Mode	Low Mode	High Mode	Low Mode
Brightness	163 lumens	12 lumens	250 lumens	24 lumens
Run Time	3.5 hours	26 hours	2.15 hours	19 hours
Beam Distance	163 meters	44 meters	151 meters	45 meters
Peak Beam Intensity	6,656 candelas	487 candelas	5,692 candelas	512 candela

Generation 3 Part Number	Generation 3 UPC Code	Generation 4 Part Number	Generation 4 UPC Code
023600-0000-110	0019428121211	023600-0001-110	0019428125189



## 2360

#### Tactical Flashlight

If you like the convenience of AA alkaline batteries, but need the performance of lithium batteries, the 2360 LED is the light for you. Using 2 standard AA alkaline batteries, the new 2360 LED emits a peak output of 375 lumens. The 2360 includes 3 modes – High / Strobe / Low and allows the user to select from 4 selectable programs. With the included 29 lumen low beam a run time of up to 13 hours will support close up use and any extended time needs. A strobe mode is also included for tactical or signaling purposes. The built-in battery level indicator ensures you will not be left in the dark.

Constructed with the most durable of materials: an aerospace grade aluminum body and an impact resistant LED lamp module, the 2360 LED keeps you on point without equipment failure.

High, Low and Strobe light output is available with a push of the tail button. It features a non-slip textured body for secure handling. The removable pocket clip offers alternative carry options.

- 4 Selectable Programs
- Pelican Products, Inc.'s Lifetime Guarantee
- 375 lumens
- 3 modes High / Strobe / Low
- Battery Level Indication
- 2 AA Batteries (included)



#### **DIMENSIONS**

Length	6.20" (15.7 cm)
--------	-----------------

#### **MATERIALS**

**Body** Aluminum with Type II Anodized

**O-Ring** EPDM

**Lens** Polycarbonate (PC)

**Shroud** Aluminum with Type II Anodized

Clip High Carbon Steel

#### **COLORS**

Black

#### LIGHT SPECS

Lamp Type LED

#### **POWER**

Battery SizeAABattery TypeAlkalineBattery Quantity2Batteries Includedyes

Battery Level Indicator Level indicator

Volts 3.0v

## WEIGHT

Weight With Batteries Weight Without

5.4 oz (153 gr) 3.7 oz (105 gr)

## **SWITCH**

Switch Type Light Modes

**Batteries** 

Momentary Push Button High / Strobe / Low

### **OTHER**

Minimum Pack Package Code 6

В

FL1 STANDARD	HIGH	LOW	
314	375 LUMENS	29 LUMENS	
	2h 30mins	13h 0mins	
	192m	53m	
	9187cd	705cd	
T	IPX8 (1m)		

## **ACCESSORIES**



**2469P** Replacement Battery

## **Technical Bulletin**



**DATE: NOVEMBER 1, 2011** 

TITLE: PELICAN UPGRADES THE PELICAN 2360 LED FLASHLIGHT

PRODUCTS AFFECTED: PELICAN 2360 LED FLASHLIGHT

#### INTRODUCTION:

To incorporate the latest LED technology and features, the 2360 LED flashlight has been upgraded with the following elements while maintaining the same price:





Light up the night with more lumen power.
Six of our best flashlights now have a substantial increase in lumen power at the current price. Get more without paying more.

Model	Previous Lumens	New Lumens	Lumens Increase	Old Part #	New Part #
1910	72	106 (Black Only)	47%	019100-0000-110	019100-0001-110
1920	120	224 (Black Only)	87%	019200-0000-110	019200-0001-110
2350	100	178	78%	023500-0000-110	023500-0001-110
2360	250	375	50%	023600-0001-110	023600-0002-110
2370	106	358	237%	023700-0000-110	023700-0001-110
2380	159	372	134%	023800-0001-110	023800-0002-110