


MODEL SPECIFICATIONS

	LED	ADJUSTABLE LED	DUAL-ILLUMINATED
MAGNIFICATION	1x	1x	1x
SIGHT WINDOW	.87 x .63 in. 22 x 16mm	.87 x .63 in. 22 x 16mm	.87 x .63 in. 22 x 16mm
LENS	Tempered Glass	Tempered Glass	Tempered Glass
ADJUSTMENTS	1 click = 1 MOA	1 click = 1 MOA	1 click = 1 MOA
ADJUSTMENT RANGE (ELEVATION & WINDAGE)	150 MOA Total Travel	150 MOA Total Travel	150 MOA Total Travel
DIMENSIONS (L x W x H)	1.8 x 1.1 x 1.0 in. 46 x 28 x 25mm	1.8 x 1.2 x 1.0 in. 46 x 30 x 25mm	1.8 x 1.2 x 1.0 in. 46 x 30 x 25mm
WEIGHT	1.2 oz. (w/ battery) 34g	1.17 oz. (w/ battery) 33.2g	1.2 oz. 34g
ILLUMINATION SOURCE	LED Powered by CR2032 Battery	LED Powered by CR2032 Battery	Tritium & Fiber Optics
BATTERY LIFE	2 years of typical use*, 5 years in dark storage	4+ years of continuous use*, at setting 4 of 8	- - -
BRIGHTNESS SETTINGS	Automatic	Automatic and 8 Adjustable Settings	Automatic
AVAILABLE MOUNTING ADAPTERS	Picatinny Rail, Weaver Rail, ACOG Add On, Riflescope Add On, Pistol, Double-Barrel Rifle	Picatinny Rail, Weaver Rail, ACOG Add On, Riflescope Add On, Pistol, Double-Barrel Rifle	Picatinny Rail, Weaver Rail, ACOG Add On, Riflescope Add On, Pistol, Double-Barrel Rifle

*When used at 70°F (21°C). Extreme temperatures (high or low) will affect lithium battery performance.




7.0 MOA Dot




9.0 MOA Dot




12.9 MOA Triangle




13.0 MOA Dot



6.5 MOA Dot



3.25 MOA Dot



1.0 MOA Dot



MADE IN THE USA 



NEW

TRIJICON RMR® TYPE 2 (Ruggedized Miniature Reflex)

The redesigned and upgraded electronics in the new RMR Type 2 passed extensive endurance testing, providing optimal performance when mounted on a pistol slide and/or other small arms platforms. Included in the new RMR Type 2 is a button lock mode, and battery saving features, which make this optic ideal for concealed carry and Law Enforcement use. The Trijicon RMR is extremely versatile as a primary optic on handguns, rifles, carbines and shotguns. When paired with a magnified optic, the RMR is an excellent solution as a secondary CQB optic, and as a backup sight.



RMR® TYPE 2* FEATURES



- **LED RMR®**
Automatically adjusts illuminated reticle to available light conditions. CR2032 battery lasts 2 years of typical use, 5 years in dark storage.

- **DEPENDABLE ELECTRONIC DESIGN**
Ruggedized battery contacts and electronics ensure performance and survivability in harsh environments.



**Compatible with all existing mounting solutions.*

- **ADJUSTABLE LED RMR®**
Features an automatic brightness mode and easy push buttons for eight adjustable brightness settings including 2 NV and 1 super bright. CR2032 battery lasts up to 4 years at a brightness setting of 4 out of 8.

- **BUTTON LOCKOUT**
Sets RMR into automatic mode to prevent accidental adjustments

- **BATTERY CONSERVATION MODE**
Automatically adjusts aiming dot to ambient lighting conditions after 16.5 hours.

GREAT FEATURES IN ALL RMR® SIGHTS

- **VERSATILE SIGHT**
Multiple primary applications including rifle, pistol, shotgun and carbine, or use as a secondary sight with a magnified optic.

- **ADJUSTABLE WINDAGE / ELEVATION**
Easily adjustable without special tools. 1 MOA per click.

- **UNIQUE PATENTED HOUSING SHAPE**
Military-grade aluminum alloy forged housing shape diverts force of impact away from the lens, greatly increasing its durability.

- **WATERPROOF TO 20 METERS (66 FT.)**

- **TRUE-COLOR MULTI-COATED LENS**
Creates a wide-band light transmission for minimal change in target area color.

- **LIMITED LIFETIME WARRANTY**
Tritium lamp is warrantied to illuminate for 15 years from date of original manufacture (Dual-Illuminated RMR). Electronics are warrantied for 5 years from date of original manufacture (LED & Adjustable LED RMR).

- **PARALLAX-FREE**



- **TRIJICON BATTERY-FREE TECHNOLOGY**
Tritium-phosphor lamp illuminates reticle in low-light conditions and fiber optics automatically adjust the brightness level and contrast to available light conditions.